



<b>MODEL</b>	F.LH-D
<b>TYPE</b>	FRAMELESS
<b>CATEGORY</b>	2 SIDED
<b>PIN CODE</b>	B1650
<b>FUEL</b>	GAS
<b>POWER (KW)</b>	
<b>HEAT INPUT</b>	
Nominal heat (hi)	12.3 KW
Reduced heat (hi)	4.9 KW
<b>HEAT OUTPUT</b>	
Nominal heat (hi)	8.9 KW
Reduced heat (hi)	3.6 KW
<b>NATURAL GAS</b>	YES
<b>PROPANE GAS</b>	YES
<b>BUTANE GAS</b>	YES
<b>SMOKE GAS EXIT /AIR INTAKE</b>	Ø 150-200MM
<b>SYSTEM</b>	
Fully remote controlled	<b>GV60 MERTIK MAXITROL®</b>

**REFERENCE GASES**

<b>SUPPLY PRESSURE</b>	<b>INJECTOR SUPPLY PRESSURE</b>	<b>RATED INJECTOR PRESSURE</b>	<b>MAIN BURNER NOZZLE DIAMETER</b>	<b>PILOT BURNER DIAMETER</b>	<b>NOMINAL CONSUMPTION</b>	<b>REDUCED CONSUMPTION</b>
37 mbar	37 mbar	6.3 mbar	1.5 mbar	0.23 mm	0.92 kg/h	0.37 kg/h