


|  |                                    |   |                     |
|--|------------------------------------|---|---------------------|
| <b>Flamme Rouge</b><br>Jbeil, Halat Main road, Bassam Bassil<br>Building, Lebanon<br><br>Brand name: ECO |                                    |  Certificate No : CE-9844 |                     |
| <b>Product Type:</b>   | Gas Fireplace                      |   |                     |
| <b>Product Name:</b>   | Frameless Gas<br>Fireplace         | <b>Serial Number</b>  |                     |
| <b>Model Type:</b>   | DIVIDER Frameless<br>Gas Fireplace | <b>Pin Code</b>   |                     |
| <b>Model Number:</b>   | F.DIV- B130                        |   |                     |
| <b>Burner included</b>   | G.BUR 122                          | <b>Burner Specifications:</b>   |                     |
|  |                                    | <u>Power:</u>   |                     |
|  |                                    | Nominal heat (hi):  | 9.8 KW              |
|  |                                    | Reduced heat (hi):  | 3.9 KW              |
|  |                                    | <u>Heat output:</u>   |                     |
|  |                                    | Nominal heat (hi):  | 7 KW                |
|  |                                    | Reduced heat (hi):  | 2.8 KW              |
|  |                                    | <u>Electrical data:</u>   |                     |
|  |                                    | Voltage rating  | 6.0V                |
|  |                                    |   |                     |
|  |                                    | Fuel:   | Propane Gas         |
|  |                                    | Gas system:   | Maxitrol syst. GV60 |
|  |                                    | Smoke Gas Exit /Air Intake:   | Ø 150-200mm         |
|  |                                    | Supply Pressure:  | 37 Mbar             |
|  |                                    | Injector Supply Pressure:   | 37 Mbar             |
|  |                                    | Rated Injector Pressure:  | 6.1Mbar             |
|  |                                    | Main Burner Nozzle Diameter:  | 1.5 Mbar            |
|  |                                    | Pilot Burner Diameter:  | 0.23 mm             |
| Nominal Consumption:   | 0.747 kg/h                         |   |                     |
| Reduced Consumption:   | 0.271 kg/h                         |   |                     |
| Burner Weight:   | 11.1 KG                            |   |                     |
| <b>Fireplace Material:</b>   | - Steel<br>-Vitro Ceramic Glass    |   |                     |
| <b>Fireplace Weight:</b>   | KG                                 |   |                     |